

CLAIMS

What is claimed is:

- 1 1. A method comprising:
2 determining a first system Advanced Configuration and Power Interface
3 Specification (ACPI) state; and
4 switching a serial Advanced Technology Attachment (SATA) device based upon
5 the ACPI state.
- 1 2. The method according to claim 1, wherein the ACPI S state is selected from the
2 group consisting of S0, S1, S2, S3, S4, and S5.
- 1 3. The method according to claim 1, wherein the switching is between two devices.
- 1 4. The method according to claim 3, wherein the two devices are the first system
2 and a subsystem.
- 1 5. The method according to claim 4, wherein:
2 if the ACPI state is S0, S1, or S2 then the SATA is switched to the first system;
3 and
4 if the ACPI state is S3, S4, or S5 then the SATA is switched to the subsystem.
- 1 6. The method according to claim 4, wherein:

2 if the ACPI state is S0, or S1 then the SATA is switched to the first system; and
3 if the ACPI state is S2, S3, S4, or S5 then the SATA is switched to the
4 subsystem.

1 7. A machine-readable medium having stored thereon instructions, which when
2 executed by a processor, causes said processor to perform the following:
3 determine a first system Advanced Configuration and Power Interface
4 Specification (ACPI) state; and
5 switch a serial Advanced Technology Attachment (SATA) based upon the ACPI
6 state.

1 8. The machine-readable medium according to claim 7, wherein switching the
2 SATA is between a plurality of devices.

1 9. A system comprising:
2 a serial Advanced Technology Attachment (SATA) device connected to a
3 switch;
4 a first system to connect to the SATA device through the switch; and
5 a subsystem to connect to the SATA device through the switch;

1 10. The system of claim 9, wherein the switch connecting the SATA device does not
2 connect both the first system and the subsystem to the SATA device simultaneously.

1 11. The system of claim 9, wherein the switch operation is controlled by signals
2 from the first system.

1 12. An apparatus comprising:
2 means for determining a first system Advanced Configuration and Power
3 Interface Specification (ACPI) state; and
4 means for switching a serial Advanced Technology Attachment (SATA) based
5 upon the ACPI state.

1 13. The apparatus of claim 12, wherein means for switching further comprises a
2 mutually exclusive switching means to a plurality of destinations.

1 14. The apparatus of claim 12, wherein the ACPI state is selected from the group
2 consisting of S0, S1, S2, S3, S4, and S5.

1 15. The apparatus of claim 12, wherein the means for switching the SATA device
2 determined whether to switch based upon signals from the first system.